

# 4048 Stack-N-Nest® System

The 4048 Stack-N-Nest System is an integrated system of 180° stack and nest containers, pallets, top caps, and dollies. Specific uses include food processing, general manufacturing, work-in-process handling, general merchandise distribution, food distribution, agricultural harvesting, and mechanical parts washing.

Attached or detached lids make these containers ideally suited for most applications.

Recommended top cap:  
40x48 GMA TOPCAP C.

Column stacks of individual sizes are vertically modular, allowing level stack heights and double stacking of pallets.


Containers available with solid or ventilated sides and bottoms for maximum air flow.

Recessed and textured identification and label areas are located on the sides, ends and cover of the container. See the Container Options on page 101.


Recommended pallet is the 40x48-B GMA CISF LPI.



# 4048 Stack-N-Nest® System



24" x 16" (1/5)  
6040 Containers



24" x 20" (1/4)  
6050 Containers



GSX6040-27 and GAX6040-27 containers feature a cross-stack and interlock bottom for a self-secured stack.

The 6050 Series has a reinforced bottom for heavy weight loads, and a patented all-plastic attached-lid hinge element to make the container 100% recyclable and rust-free.

All containers available with smooth bottom for easy cleaning, or textured bottom for conveyor system use.

ESD materials available upon request.

Check the ORBIS website for current Ship-From-Stock SKU availability.

Specifications													All dimensions in inches, unless specified.	
Model	Modularity on GMA 48" x 40" pallet	Outside Top Dimensions		Inside Bottom Dimensions		Total Container Height	Product Clearance		Weight (lb.)	Volume (cu. ft.)	Nest Ratio	53' Trailer Truckload Quantities		
		L	W	L	W		w/ Cover	w/o Cover						
<b>CONTAINERS</b>														
GS6040-13	1/5	23.6	15.8	19.3	13.4	5.3	5.2	4.4	2.8	0.8	3.0:1	7,200		
GS6040-18	1/5	23.6	15.8	19.3	13.4	7.1	7.0	6.2	3.2	1.0	3.0:1	5,184		
GS6040-22	1/5	23.6	15.8	19.3	13.4	8.5	8.4	7.6	3.6	1.3	3.0:1	4,608		
GS6040-27	1/5	23.6	15.8	19.3	13.4	10.7	10.6	9.8	4.2	1.6	3.0:1	3,456		
GS6040-36	1/5	23.6	15.8	19.3	13.4	14.3	13.2	13.0	5.2	2.1	3.0:1	2,592		
GS6050-18	1/4	23.6	19.7	18.2	16.8	7.6	6.8	6.8	4.0	1.2	3.4:1	5,520		
GS6050-27	1/4	23.6	19.7	18.2	16.8	11.2	10.2	10.2	4.9	1.8	4.0:1	3,600		
GS6050-36	1/4	23.6	19.7	18.2	16.8	14.8	13.9	13.9	5.8	2.5	4.0:1	2,640		
<b>REINFORCED BOTTOM CONTAINERS</b>														
GSX6040-27	1/5	23.6	15.8	19.3	13.4	11.3	10.0	10.6	4.9	1.6	3.0:1	3,456		
GS6050-18	1/4	23.6	19.7	18.2	16.8	7.6	6.5	6.5	4.8	1.1	3.4:1	5,520		
GS6050-27	1/4	23.6	19.7	18.2	16.8	11.2	9.9	9.9	5.6	1.8	4.0:1	3,600		
GS6050-36	1/4	23.6	19.7	18.2	16.8	14.8	13.6	13.6	6.5	2.4	4.0:1	2,640		
<b>COVERS</b>														
CGS6040	N/A	24.0	16.1	N/A	N/A	1.3	N/A	N/A	1.8	N/A	1.0:1	N/A		
CGS6050	N/A	23.6	19.6	N/A	N/A	0.9	N/A	N/A	1.9	N/A	1.0:1	N/A		
<b>ATTACHED LID CONTAINERS</b>														
GA6040-22	1/5	23.6	15.8	19.2	13.4	9.2	8.1	N/A	5.6	1.2	3.0:1	3,584		
GA6040-27	1/5	23.6	15.8	19.2	13.4	11.3	10.2	N/A	5.9	1.5	3.0:1	2,688		
GA6040-36	1/5	23.6	15.8	19.2	13.4	14.9	13.8	N/A	6.8	2.0	3.0:1	2,100		
GA6050-27	1/4	23.6	19.7	18.2	16.8	11.2	10.2	N/A	7.1	1.8	4.0:1	2,640		
GA6050-36	1/4	23.6	19.7	18.2	16.8	14.8	13.9	N/A	8.0	2.5	4.0:1	2,160		
<b>REINFORCED BOTTOM, ATTACHED LID CONTAINERS</b>														
GAX6040-27	1/5	23.6	15.8	19.3	13.4	11.9	10.2	N/A	6.8	1.5	3.0:1	2,688		
GA6050-27	1/4	23.6	19.7	18.2	16.8	11.2	9.9	N/A	7.7	1.8	4.0:1	2,640		
GA6050-36	1/4	23.6	19.7	18.2	16.8	14.8	13.6	N/A	8.6	2.4	4.0:1	2,160		