



- ASSEMBLY NOTES:
- 1) DOUBLE-RIVET BEAMS ARE HAMMERED INTO POSTS AT TOP AND BOTTOM OF UNIT FOR RIGIDITY. USE THREE LEVELS OF QDR'S ON UNITS 10' TALL AND OVER.
 - 2) SINGLE-RIVET BEAMS (QSR) SUPPORT INTERMEDIATE SHELVES.
 - 3) T-POSTS (QTP) JOIN UNITS IN A CONTINUOUS ROW. ANGLE POSTS (QP) USED AT END OF EACH ROW.
 - 4) ALLOW FOR 3/4" GROWTH IN WIDTH AND A 1/2" GROWTH IN DEPTH FOR EACH UNIT. (FOR EXAMPLE: IF YOU ORDER 48" WIDE X 24" DEEP UNITS, THE ACTUAL DIMENSIONS WILL BE 48 3/4" WIDE X 24 1/2" DEEP.)
 - 5) UNITS 24" DEEP OR LESS DO NOT REQUIRE INTERMEDIATE BEAMS RUNNING FRONT TO BACK.

TEILHABER MANUFACTURING CORPORATION
 2360 INDUSTRIAL LANE • BROOMFIELD, COLORADO 80020 • (303)466-2323

SCALE: N.T.S.
 DR. BY: RLB
 DATE: 3/30/07

THIS DRAWING AND/OR ITS CONTENTS, INFORMATION, AND PRINCIPALS OF DESIGN ARE THE EXCLUSIVE PROPERTY OF TEILHABER MANUFACTURING CORPORATION, AND IS SUBMITTED TO YOU WITH THE AGREEMENT THAT IT IS NOT TO BE REPRODUCED IN ANY MANNER, COPIED, OR MODIFIED, NOR IS IT TO BE RELAYED IN PART OR IN WHOLE FOR ANY OTHER PROJECT OR EXTENSION OF THIS PROJECT EXCEPT BY WRITTEN AGREEMENT WITH TEILHABER MANUFACTURING CORPORATION. ACCEPTANCE OF THIS DRAWING WILL BE CONSTRUED AS AN AGREEMENT TO THIS STATEMENT.

DRAWING NO.		96-60	
DISTRIBUTOR:		NAME OF PROJECT:	
NO. DR. BY		PROJECT LOCATION:	
REVISION		DATE	
NO. DR. BY		DESCRIPTION: STANDARD DUTY STARTER UNIT	
1 of 1		SHEET	
B			

This is a Standard duty starter unit with 5 shelves