



WORKHORSE™

250% PRE-STRETCH PALLET WRAPPER

Diameter of Turntable	59"
Turntable Speed	Adjustable up to 12 rpm
Film Carriage Speed	Adjustable up to 3.5"/sec
Maximum Wrap Height	82" Standard / 100" Optional
Load Weight Capacity	5,000 lbs.
Maximum Load Size (LxWxH)	52" x 52" x 80" or 100"
Film Width	20"
Control System	Programmable
Power Supply	110V / 60HZ / 1Phase
Dimensions of Machine (LxWxH)	59.4" x 98.4" x 102.4"
Machine Weight	890 lbs.

XT-4505 & XT-4502 Features:

- Mast heights of 82" (XT4505) & 100" (XT-4502).
- Easy to use control panel.
- 250% Pre-Stretch
- Precise phase stopping at cycle end.
- Front and rear fork life pick up points.
- Soft start and stop.
- Folding mast column for easy installation and shipment.
- 1 year parts warranty.
- **Optional entry / exit ramp available - for loading by pallet jack.**

Pre-Stretch Carriage:

- 250% Stretch.
- Easy film force to load.
- Auto height sensor.

Easy to Program Control Panel

Adjustable Parameters:

- Top and Bottom pallet wrapping wraps from 0-10.
- Rotation speed from 0 to 12 rpm.
- Film carriage speed.
- Photoeye sensing for load height.
- Top sheet cycle.

Selectable Cycles:

- Double cycle (upward and downward).
- Single cycle (only upward or only downward).
- Wrapping cycle with fixed point reinforcement.
- Wrapping cycle with manual control and override.



Optional Digital Scale with 1" numbers for readout:

- 5,000 lb capacity.
- 4 stainless steel heavy duty load cells.
- 2 load cells are hidden under turntable for safety.
 - Pounds and kilograms capable.
 - Plus or minus 2 lbs for tolerance and accuracy.
- 3/4" steel plate for holding load cells, and for longevity.
 - RS-232 port for printing.
- Flexible cord for Display, 15 feet cord length for mounting options.

DACO

(877) 247-3834 - dacocorp.com